


## RR KABEL FR HSF / FR-LSH / LSOH-FR


  
RR KABEL

RR Kabel makes single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC/FR-LSH PVC/ Thermoplastic Halogen free Flame Retardant (HFFR) 70° Insulated Industrial Cables in voltage grade upto and including 1100 Volts ( HSN Code : 8544)

RATE / 100 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR HSF FR PVC INSULATION As Per IS 694	RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694	RR KABEL LSOH-FR <small>Thermoplastic Halogen Free Flame Retardant (HFFR) 70° C Insulation As Per IS 17048</small>
10.0	140/0.3	52	21019	21751	23092
16.0	126/0.4	70	33270	34430	36368
25.0	196/0.4	88	53730	55880	60181
35.0	276/0.4	112	75161	78167	84178
50.0	396/0.4	146	107187	111472	120047
70.0	360/0.5	216	151901	157977	170127
95.0	480/0.5	262	204341	212515	228862
120.0	608/0.5	310	264401	274981	296132
150.0	750/0.5	355	327760	340874	367090
185.0	931/0.5	415	398619	414565	446451
240.0	1200/0.5	500	524417	545393	587347
300.0	1500/0.5	550	654683	680873	733245
400.0 *	2013/0.5	590	889625	925212	996380
500.0 *	2562/0.5	660	1153166	1199290	1291544
630.0 *	3416/0.5	725	1532893	1594208	1716840

The item marked \* are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

\*\* RR Kabel LSOH-FR: Insulation conforming to HFI TP 70 as per IS 17048

## RR KABEL FR HSF SINGLE CORE


  
RR KABEL

Multistrand bright electrolytic annealed bare copper conductor, FR PVC Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts as per IS 694 ( HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Rate Per 100 Mtr
0.5	16/0.2	5	1205
0.75	24/0.2	8	1694
1.0	32/0.2	13	2207
1.5	30/0.25	17	3192
2.5	50/0.25	24	5200
4.0	56/0.3	30	7949
6.0	84/0.3	38	11826