

SUPEREX FR FR PVC Insulated Single Core Cables



RR Kabel makes Single Core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
0.75	24/0.2	1417	24
1.0	14/0.3	1931	24
1.5	22/0.3	2815	16
2.5	36/0.3	4505	12
4.0	56/0.3	6565	8
6.0	84/0.3	9781	4

UNILAY HR FR HR FR PVC Insulated Single Core Cables



RR Kabel makes Single Core unsheathed Multistrand flexible High Conductivity plain annealed copper, HR FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.0	37/0.19	2023	24
1.5	37/0.23	2941	16
2.5	61/0.23	4715	12
4.0	61/0.29	7202	8
6.0	91/0.29	10706	4

FIREX LSOH HALOGEN FREE FLAME RETARDANT 90°C, CROSSLINKED



RR Kabel makes Single Core unsheathed Multistrand High Conductivity plain annealed Copper, Cross linked Halogen Free Flame Retardant (HFFR) 90° C Insulated Industrial Cables in voltage grade upto and including 1100 volts, as per IS 17048 (HSN Code: 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.00	14/0.3	2378	24
1.50	22/0.3	3350	16
2.50	36/0.3	5307	12
4.00	56/0.3	7788	8
6.00	84/0.3	11281	4

* FIREX LSOH - Insulation Conforming to HFI XL 90 as per IS 17048