


## RR KABEL FR HSF / FR-LSH


  
RR KABEL

RR Kabel makes Single Core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC/FR-LSH PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 694 (HSN Code: 8544)

RATE / 200 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR HSF FR PVC INSULATION	RR KABEL FR-LSH FR-LSH PVC INSULATION	No. of Coils packed in an Outer Box
0.75	24/0.2	8	3407	3523	12
1.0	32/0.2	13	4448	4604	12
1.5	30/0.25	17	6432	6652	8
2.5	50/0.25	24	10472	10840	6
4.0	56/0.3	30	16098	16664	4
6.0	84/0.3	38	23941	24718	2

## LSOH-FR


  
RR KABEL

RR Kabel makes Multistrand High Conductivity Plain Copper Thermoplastic Halogen Free Flame Retardent (HFFR) 70° C Insulated Single Core Unsheathed Industrial Cables in Voltage Grade Upto and Including 1100 Volts, As Per IS 17048 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Unit	Rate	No. of Coils packed in an Outer Box
0.75	24/0.2	8	180 Mtr	3430	12
1.0	32/0.2	13	180 Mtr	4322	12
1.5	30/0.25	17	180 Mtr	6080	8
2.5	50/0.25	24	180 Mtr	9840	6
4.0	56/0.25	30	180 Mtr	15088	4
6.0	84/0.3	38	180 Mtr	22372	2

## FR HSF


  
RR KABEL

RR Kabel makes Multistrand High Conductivity Plain Copper FR PVC Insulated Single Core Unsheathed Industrial Cables in Voltage Grade Upto and Including 1100 Volts, As Per IS 694 (HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Unit	Rate	No. of Coils packed in an Outer Box
0.75	24/0.2	8	180 Mtr	2870	12
1.0	32/0.2	13	180 Mtr	3751	12
1.5	30/0.25	17	180 Mtr	5423	8
2.5	50/0.25	24	180 Mtr	8850	6
4.0	56/0.25	30	180 Mtr	13542	4
6.0	84/0.3	38	180 Mtr	20134	2