

SUPEREX FR

FR PVC Insulated Single Core Cables



Single Core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

| Size (Sq.mm) | Configuration | Rate/90 mtr | No. of Coils packed in an Outer Box |
|--------------|---------------|-------------|-------------------------------------|
| 0.75 | 24/0.2 | 1533 | 24 |
| 1.0 | 14/0.3 | 2090 | 24 |
| 1.5 | 22/0.3 | 3046 | 16 |
| 2.5 | 36/0.3 | 4855 | 12 |
| 4.0 | 56/0.3 | 7067 | 8 |
| 6.0 | 84/0.3 | 10556 | 4 |

UNILAY HR FR

HR FR PVC Insulated Single Core Cables



Single Core unsheathed Multistrand flexible High Conductivity plain annealed copper, HR FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

| Size (Sq.mm) | Configuration | Rate/90 mtr | No. of Coils packed in an Outer Box |
|--------------|---------------|-------------|-------------------------------------|
| 1.0 | 37/0.19 | 2189 | 24 |
| 1.5 | 37/0.23 | 3183 | 16 |
| 2.5 | 61/0.23 | 5102 | 12 |
| 4.0 | 61/0.29 | 7793 | 8 |
| 6.0 | 91/0.29 | 11585 | 4 |

FIREX LSOH - EBXL

E-Beam Crosslinked Halogen Free Flame Retardant



Single Core unsheathed Multistrand High Conductivity plain annealed Copper, E-Beam Cross linked Halogen Free Flame Retardant (HFFR) Insulated Industrial Cables in voltage grade upto and including 1100 volts, as per IS 17048 (HSN Code: 8544)

| Size (Sq.mm) | Configuration | Rate/90 mtr | No. of Coils packed in an Outer Box |
|--------------|---------------|-------------|-------------------------------------|
| 0.75 | 24/0.2 | 1648 | 24 |
| 1.00 | 14/0.3 | 2340 | 24 |
| 1.50 | 22/0.3 | 3379 | 16 |
| 2.50 | 36/0.3 | 5410 | 12 |
| 4.00 | 56/0.3 | 7814 | 8 |
| 6.00 | 84/0.3 | 11640 | 4 |

* FIREX LSOH - EBXL - Insulation Conforming to HFI-XL 90 as per IS 17048