

**FR HSF**

RR KABEL

Single Core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 694 (HSN Code: 8544)

Size (Sq.mm)	Configuration	AMPS	Unit	Rate	No. of Coils packed in an Outer Box
0.75	24/0.2	8	200 Mtr	3686	12
1.0	32/0.2	13	200 Mtr	4813	12
1.5	30/0.25	17	200 Mtr	6961	8
2.5	50/0.25	24	200 Mtr	11331	6
4.0	56/0.25	30	200 Mtr	17420	4
6.0	84/0.3	38	200 Mtr	25908	2

**RR KABEL FR-LSH**

RR KABEL

Single Core unsheathed Multistrand High Conductivity plain annealed copper, FR-LSH PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 694 (HSN Code:8544)

Size (Sq.mm)	Configuration	AMPS	Unit	Rate	No. of Coils packed in an Outer Box
0.75	24/0.2	8	200 Mtr	3812	12
1.0	32/0.2	13	200 Mtr	4982	12
1.5	30/0.25	17	200 Mtr	7199	8
2.5	50/0.25	24	200 Mtr	11731	6
4.0	56/0.25	30	200 Mtr	18032	4
6.0	84/0.3	38	200 Mtr	26747	2

**LSOH-EBXL**

RR KABEL

Single Core unsheathed Multistrand High Conductivity plain annealed copper, E-Beam cross-linked Halogen Free Flame retardant (HFFR) Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 17048 (HSN Code:8544)

Size (Sq.mm)	Configuration	AMPS	Unit	Rate	No. of Coils packed in an Outer Box
0.75	24/0.2	13	200 Mtr	4246	12
1.0	32/0.2	21	200 Mtr	5349	12
1.5	30/0.25	27	200 Mtr	7525	8
2.5	50/0.25	34	200 Mtr	12179	6
4.0	56/0.25	46	200 Mtr	18675	4
6.0	84/0.3	59	200 Mtr	27691	2