



RR KABEL FR HSF / FR-LSH / LSOH-FR



Single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC/FR-LSH PVC/ Thermoplastic Halogen free Flame Retardant (HFFR) 70° Insulated Industrial Cables in voltage grade upto and including 1100 Volts (HSN Code : 8544)

RATE / 100 MTR					
Size (Sq.mm)	** Configuration	AMPS	RR KABEL FR HSF FR PVC INSULATION As Per IS 694	RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694	RR KABEL LSOH-FR Thermoplastic Halogen Free Flame Retardant (HFFR) 70° C Insulation As Per IS 17048
10.0	140/0.3	52	27288	28240	29980
16.0	126/0.4	70	43193	44700	47215
25.0	196/0.4	88	69087	71850	77383
35.0	276/0.4	112	96642	100506	108237
50.0	396/0.4	146	137823	143331	154356
70.0	360/0.5	216	195315	203127	218750
95.0	480/0.5	262	262742	273253	294271
120.0	608/0.5	310	339968	353572	380768
150.0	750/0.5	355	421435	438297	472006
185.0	931/0.5	415	512546	533051	574047
240.0	1200/0.5	500	674297	701267	755212
300.0	1500/0.5	550	841793	875468	942809
400.0 *	2013/0.5	590	1143882	1189641	1281148
500.0 *	2562/0.5	660	1482744	1542051	1660670
630.0 *	3416/0.5	725	1970998	2049837	2207518

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

RR Kabel LSOH-FR: Insulation conforming to HFI TP 70 as per IS 17048

* As per IS 8130

RR KABEL FR HSF SINGLE CORE



Multistrand bright electrolytic annealed bare copper conductor, FR PVC Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts as per IS 694 (HSN CODE : 8544)

Size (Sq.mm)	* Configuration	AMPS	Rate Per 100 Mtr
0.5	16/0.2	5	1576
0.75	24/0.2	8	2216
1.0	32/0.2	13	2886
1.5	30/0.25	17	4175
2.5	50/0.25	24	6800
4.0	56/0.3	30	10396
6.0	84/0.3	38	15466

* As per IS 8130