

## BRAIDED CABLES



Flexible / Stranded Bare Copper Conductor, PVC Insulated, Annealed Tinned Copper Braided with Optimum coverage and Outer PVC sheathed Industrial Braided cables, Voltage Grade 300/500V.

Size in Sq.mm / Rate Per 100 Meter (in INR)						
SIZE	0.25	0.50	0.75	1.00	1.50	2.50
2 Core	10801	12438	13502	15282	19485	28523
3 Core	11618	13875	16770	19302	25189	37445
4 Core	13971	16970	20779	24438	31512	48027
5 Core	17498	19824	24876	29129	38507	-
6 Core	20611	21889	26320	33047	43239	-
7 Core	21757	23763	30347	36471	48800	-
8 Core	23311	26804	33971	41538	56373	-
9 Core	-	-	-	-	63067	-
10 Core	27853	34047	43163	51433	70067	-
12 Core	30865	37033	49511	60179	81612	-
14 Core	-	42426	56506	69620	94680	-
16 Core	-	47756	63702	78361	106602	-
18 Core	43436	52701	71402	87657	112793	-

Size in Sq.mm / Rate Per 100 Meter (in INR)				
SIZE	4.0	6.0	10.0	16.0
2 Core	41175	56746	-	-
3 Core	56528	78625	-	-
4 Core	71166	100269	168332	272322

Note : Please contact HO for Technical Data Sheet.

Note : Minimum Order Quantity (MOQ)

Size - upto 0.25 x 8C - 5 KM, upto 0.25 x 8C to 18C and 0.50 to 1.50 x 7C - 3 KM,  
0.50 x 8C to 4.0 x 4C - 2 KM, 0.50 x 22C to 1.00 x 27C - 2 KM.