

FIREX LSOH - EBXL
HFFR • E-BEAM CROSSLINKED



Single core unsheathed multistrand high conductivity plain annealed copper, E-Beam Cross linked Halogen Free Flame Retardant (HFFR) insulated industrial cables in voltage grade up to and including 1100 volts, as per IS 17048 (HSN CODE: 8544)

DOES NOT MELT UP TO 900°C
DOUBLE LOAD • DOUBLE LIFE



BUILT TO LAST



ALL WEATHER READY



PEST RESISTANT



Size (Sq.mm)	* Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
0.75	24/0.21	1900	24
1.00	32/0.21	2587	24
1.50	30/0.26	3761	16
2.50	50/0.26	6005	12
4.00	56/0.31	8849	8
6.00	84/0.31	13148	4

* As per IS 8130

SUPEREX GREEN HR+FR



Single core unsheathed multistrand high conductivity plain annealed copper, HR+FR PVC insulated industrial cables in voltage grade up to and including 1100 volts, as per IS 694 (HSN CODE: 8544)

WITH HEAT GUARD TECHNOLOGY
TRULY GREEN WIRE



BUILT TO LAST



ALL WEATHER READY



PEST RESISTANT



EXTENSIVE LOAD CAPACITY



Size (Sq.mm)	* Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
0.75	24/0.21	1821	24
1.0	14/0.31	2483	24
1.5	22/0.31	3619	16
2.5	36/0.31	5770	12
4.0	56/0.31	8398	8
6.0	84/0.31	12543	4

* As per IS 8130