

## FR HSF



Single Core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 694 (HSN Code: 8544)

Size (Sq.mm)	* Configuration	AMPS	Unit	Rate	No. of Coils packed in an Outer Box
0.75	24/0.2	8	200 Mtr	4453	12
1.0	32/0.2	13	200 Mtr	5816	12
1.5	30/0.25	17	200 Mtr	8412	8
2.5	50/0.25	24	200 Mtr	13693	6
4.0	56/0.30	30	200 Mtr	21053	4
6.0	84/0.3	38	200 Mtr	31308	2

\* As per IS 8130

## RR KABEL FR-LSH



Single Core unsheathed Multistrand High Conductivity plain annealed copper, FR-LSH PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 694 (HSN Code:8544)

Size (Sq.mm)	* Configuration	AMPS	Unit	Rate	No. of Coils packed in an Outer Box
0.75	24/0.2	8	200 Mtr	4607	12
1.0	32/0.2	13	200 Mtr	6021	12
1.5	30/0.25	17	200 Mtr	8700	8
2.5	50/0.25	24	200 Mtr	14176	6
4.0	56/0.30	30	200 Mtr	21790	4
6.0	84/0.3	38	200 Mtr	32322	2

\* As per IS 8130

## LSOH-EBXL



Single Core unsheathed Multistrand High Conductivity plain annealed copper, E-Beam cross-linked Halogen Free Flame retardant (HFFR) Insulated Industrial Cables in voltage grade upto and including 1100 Volts, As per IS 17048 (HSN Code:8544)

Size (Sq.mm)	* Configuration	AMPS	Unit	Rate	No. of Coils packed in an Outer Box
0.75	24/0.2	13	200 Mtr	5130	12
1.0	32/0.2	21	200 Mtr	6464	12
1.5	30/0.25	27	200 Mtr	9094	8
2.5	50/0.25	34	200 Mtr	14719	6
4.0	56/0.30	46	200 Mtr	22567	4
6.0	84/0.3	59	200 Mtr	33463	2

\* As per IS 8130