

SUPEREX FR FR PVC Insulated Single Core Cables



RR Kabel make single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN Code: 8544)

| Size (Sq.mm) | Configuration | Rate/90 mtr | No. of Coils packed in an Outer Box |
|--------------|---------------|-------------|-------------------------------------|
| 0.75 | 24/0.2 | 1195 | 24 |
| 1.0 | 14/0.3 | 1622 | 20 |
| 1.5 | 22/0.3 | 2365 | 12 |
| 2.5 | 36/0.3 | 3776 | 12 |
| 4.0 | 56/0.3 | 5505 | 8 |
| 6.0 | 84/0.3 | 8201 | 4 |
| 10.0 | 140/0.3 | 15044 | 3 |
| 16.0 | 126/0.4 | 24161 | 2 |

UNILAY HR FR HR FR PVC Insulated Single Core Cables



RR Kabel make single core unsheathed Multistrand Flexible High Conductivity plain annealed Copper, HR FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN Code: 8544)

| Size (Sq.mm) | Configuration | Rate/90 mtr | No. of Coils packed in an Outer Box |
|--------------|---------------|-------------|-------------------------------------|
| 1.0 | 37/0.19 | 1710 | 20 |
| 1.5 | 37/0.23 | 2482 | 12 |
| 2.5 | 61/0.23 | 3975 | 12 |
| 4.0 | 61/0.29 | 6066 | 8 |
| 6.0 | 91/0.29 | 9018 | 8 |

FLAMEX FR-LSH FR-LSH PVC Insulated Single Core Cables



RR Kabel make single core unsheathed Multistrand High Conductivity plain annealed Copper, FR-LSH PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN Code: 8544)

| Size (Sq.mm) | Configuration | Rate/90 mtr | No. of Coils packed in an Outer Box |
|--------------|---------------|-------------|-------------------------------------|
| 1.0 | 14/0.3 | 1693 | 20 |
| 1.5 | 22/0.3 | 2484 | 12 |
| 2.5 | 36/0.3 | 3958 | 12 |
| 4.0 | 56/0.3 | 5780 | 8 |
| 6.0 | 84/0.3 | 8582 | 4 |