

## RR KABEL FR / FR-LSH / LSOH



RR KABEL make single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC / FR-LSH PVC / Thermoplastic Halogen Free Flame Retardant (HFFR) 70 °C Insulated Industrial Cables in voltage grade upto and including 1100 Volts (HSN Code: 8544)

RATE / 100 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR FR PVC INSULATION As Per IS 694	RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694	RR KABEL LSOH Thermoplastic Halogen Free Flame Retardant (HFFR) 70 °C Insulation As Per IS 17048
10.0	140/0.3	52	16874	17466	18539
16.0	126/0.4	70	26714	27644	29200
25.0	196/0.4	88	42687	44394	47809
35.0	276/0.4	112	59710	62099	66875
50.0	396/0.4	146	84341	87715	94462
70.0	360/0.5	216	120675	125502	135157
95.0	480/0.5	262	161583	168046	180972
120.0	608/0.5	310	209075	217438	234164
150.0	750/0.5	355	259175	269542	290276
185.0	931/0.5	415	318266	330996	356458
240.0	1200/0.5	500	414680	431267	464441
300.0	1500/0.5	550	517688	538395	579810
400.0 *	2013/0.5	590	717260	745951	803331
500.0 *	2562/0.5	660	911858	948333	1021281
630.0 *	3416/0.5	725	1212127	1260612	1357582

The item marked \* are non stock items refer to marketing dept for delivery schedule MOQ packing etc.

\*RR KABEL LSOH – Insulation conforming to HFI TP 70 as per IS 17048

## RATNA FLEX SINGLE CORE



Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts (HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Rate Per 100 Mtr
0.5	16/0.2	5	952
0.75	24/0.2	8	1372
1.0	32/0.2	13	1770
1.5	30/0.25	17	2559
2.5	50/0.25	24	4136
4.0	56/0.3	30	6490
6.0	84/0.3	38	9615